Baxter

Likorall

OVERHEAD LIFT

LIKORALL OVERHEAD LIFT

The **Likorall** lift is designed for user-friendly operation while focusing on safety. This thoughtful design helps the **Likorall** be a good solution in a variety of healthcare settings.

PEACE OF MIND FOR YOUR LIFTING NEEDS

- Mechanical or electrical emergency lowering available
- Patented safety drum is designed to help ensure even, controlled lowering.
- Safety Squeeze Protection Limit Switch is designed to help protect the lift motor from mechanical strain and may help prevent injuries to patients and caregivers
- Room-to-room (R2R) model is designed to help you efficiently move patients between rooms without a continuous rail connection
- The hand control - available on the ES model - is designed to help you navigate through rail switches and change of patient direction with turntables.
- **UltraTwin** ceiling mounted lift system consists of two **Likorall** lift motors that provide a combined lifting capacity.
- Safe Working Load
  - Standard models: 200-250 kg / 440-550 lb, depending on model
  - **UltraTwin** model: 400-500 kg / 882-1,102 lb, depending on model

MOVING THE LIFT MOTOR

The Quick-Release Hook Carriage supports moving the system between rooms.

IN-RAIL CHARGING (**Likorall** 250 S IRC only)

The lift unit constantly charges along the complete rail system, to help ensure it's ready for use when needed.

AVAILABLE MODELS

Likorall Overhead Lift Systems 200 | 242 S, S R2R, ES, ES R2R 250 ES, S IRC

	LR200	LR242 S	LR242 S R2R	LR242 ES	LR242 ES R2R	LR250 ES	LR250 S IRC
Maximum Weight Capacity	200 kg / 440 lb	200 kg / 440 lb	200 kg / 440 lb	200 kg / 440 lb	200 kg / 440 lb	250 kg / 550 lb	250 kg / 550 lb
Lift Interval	2050 mm	2050 mm	2050 mm	2050 mm	2050 mm	2050 mm	2050 mm
Lift Speed	50 mm/s	50 mm/s	50 mm/s	50 mm/s	50 mm/s	50 mm/s	50 mm/s
Battery Technology	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid
Quick Release Hook (W/O adapter)	X		X		X	X	X
Electrical Emergency Lowering	X	X	X	X	X	X	X
Manual Emergency Lowering		X		X			
Electrical Emergency Lowering Reachable From Floor	X						
Manual Emergency Lowering Reachable From Floor		X		X			
Room-to-Room	X		X		X	X	
Fixed Hook (W/O adapter)		X		X			
In-Rail Charging							X
Transfer Motor Compatibility				X		X	
Weight of Motor	12.5 kg / 27.6 lb	13 kg / 28.6 lb	12.6 kg 27.7 lb	13 kg / 28.6 lb	12.6 kg / 27.7 lb	12.6 kg / 27.7 lb	12.6 kg / 27.7 lb
Dimensions (L x W x H)	340 mm x 250 mm x 165 mm / 13.39" x 9.84" x 6.5"						

For more information, please contact your Baxter sales representative.

For safe and proper use of the product mentioned herein, please refer to the appropriate Operator's Manual or Instructions for Use.

Baxter reserves the right to make changes without notice in design, specifications and models. The only warranty Baxter makes is the express written warranty extended on the sale or rental of its products.

bax.to/sphm

Baxter, Likorall and UltraTwin are trademarks of Baxter International Inc. or its subsidiaries.

US-CS125-250004 (v1.0) 04/2025